

V2 TRACTION

EASY FIT SNOW CHAINS

Anti Rust Diamond Pattern

FITTING & REMOVAL INSTRUCTIONS



- Remove chains from the bag. Unhook the flexible hoop & spread the chains out on the road. Ensure all connections are undone & there are no twists or tangles in the chains, this step is important for ease of fitting.
- Pass the **yellow** end of the flexible cable around the back of the tyre right to left. Try to avoid the chains touching the tyre in this step, so you don't snag any of the chain between the tyre & the road.



- Pick up the ends of the flexible cable and join them together on the top of the tyre. Try to keep the chain links in front of your hands as in the photo so they do not drop behind the back of the wheel.

To ensure a correct fit, Chains must be tried on the vehicle before departure



- Join the side chain & blue hook together on the top sidewall of the tyre



- Make sure to push the flexible cable right over to the back of the tyre wall & off the tyre tread.



- Connect the tension chain with rubber hook to the auto locking lever at the bottom of the wheel & tighten firmly. Check the flexible cable is running evenly around the inside wall of the tyre & is clear of any suspension components. (Important)
- Using both hands grasp the side chains on the tyre wall & wriggle them backwards & forwards around the tyre to bed the chains in, re tighten & take up any extra slack with the Auto locking lever.
- If there is not enough tension chain left for re tightening, go back to instruction 4 & connect the 2nd or 3rd chain link to the blue hook on the top sidewall of the tyre.



- Check the side chain is running evenly around the sidewall of the tyre, this ensures the flexible cable on the inside of the tyre is doing the same. Connect the tension chain with the rubber hook to one or both red hooks, then secure firmly to the side chain.
- Once these steps have been completed and the chains are evenly and firmly fitted to each of the drive wheels, drive forward slowly for 20 mtrs to bed the chains in, then release tension chain from side chain & red hooks, retighten firmly using the auto locking lever then firmly reconnect tension chain to red hooks & side chain.



- To remove the chains stop each wheel in the same position the chains were fitted, with the autolock lever at the bottom of the wheel as in the photo, then reverse the installation steps in order.
When you have disconnected the chain off the tyre make sure it is laying flat on the road, then drive forward to clear the chains.

PLEASE NOTE: While driving in the snow with chains fitted you must drive carefully, avoid sudden acceleration or sudden stops and never exceed 50 km/h.

Warning: Failure to fit chains firmly & correctly could result in damage to vehicle & chains.

www.xswinter.com